Amphenol

Cable & Interconnect Technologies

Wire & Cable

## **ECS Avionics RF Cable**

P/N 532101 | 50  $\Omega$  Coaxial



## INTRODUCTION

Our ECS Brand Avionics RF cables are optimized specifically for avionics systems that require a low-loss, lightweight, halogen-free cable with frequencies between 0 - 12 GHz. Sold in bulk, as finished assemblies, or within an application-specific kit, these cables have short lead times and are often in stock with same-day shipping available.

## **ENVIRONMENTAL DETAILS**

- » Designed to meet or exceed burn requirements as set forth in Federal Aviation Regulations 14 CFR Part 25.869(a)(4) Amdt 25-113, Appendix F Part I(a)(3).
- » Manufactured with materials which, when subjected to flames or high temperatures, will not outgas deadly hydrogen chloride produced by conventional PVC cables.

| CONNECTOR TYPE            | P/N                |
|---------------------------|--------------------|
| ARINC 404 Size 1          | Use LMT101 Adapter |
| ARINC 600 Size 1          | L5122              |
| ARINC 600 Size 1 Modified | M5122              |
| ARINC 600 Size 5          | P522               |
| ARINC 600 Size 8          | N/A                |
| BNC 90°                   | CBR522             |
| BNC 90° Extended          | N/A                |
| BNC 90° Long              | N/A                |
| BNC Bulkhead              | BBS522             |
| BNC Straight              | CBS522             |
| C 90°                     | CCR522             |
| C Straight                | CCS522             |
| HN 90°                    | N/A                |
| N 90°                     | CNR522             |
| N Bulkhead                | BNS522             |
| N Straight                | CNS522             |
| SMA 90°                   | CSR522             |
| SMA Straight              | CSS522             |
| TNC 90°                   | CTR522             |
| TNC 90 Self-Locking       | CLTR522            |
| TNC 90° Extended          | N/A                |
| TNC 90° Long              | N/A                |
| TNC Bulkhead              | BTS522             |
| TNC Panel Mount           | RTS522             |
| TNC Straight              | CTS522             |
| TNC Straight Self-Locking | CLTS522            |

| PHYSICAL CHARACTERISTICS (NOMINAL)                                |             |                                      |
|---|-------------|--------------------------------------|
| Outer Diameter  |             | 0.130"                               |
| Minimum Bend Radius   |             | 0.65"                                |
| Weight  |             | 1.55 lb/100 ft                       |
| Temperature Range   |             | -55 to 200 °C                        |
| Skydrol™ Resistant  |             | Yes                                  |
| ELECTRI   | CAL CHARA   | CTERISTICS (NOMINAL)                 |
| Impedance   |             | 50 Ω                                 |
| Capacitance   |             | 27 pF/ft                             |
| DC Resistance   |             | 14.80 Ω/1,000 ft                     |
| Time Delay  |             | 1.34 ns/ft                           |
| Velocity of Propagation   |             | 76%                                  |
| Shield Effectiveness  |             | > 80 dB                              |
| Attenuation   | @ 150 MHz   | 6.4 dB/100 ft                        |
|   | @ 1,000 MHz | 17.4 dB/100 ft                       |
|   | @ 1,600 MHz | 21.8 dB/100 ft                       |
|   | @ 2,400 MHz | 25.7 dB/100 ft                       |
|   | @ 5,000 MHz | 39.0 dB/100 ft                       |
| CONSTRUCTION DETAILS  |             |                                      |
| Conductor   |             | 22 AWG stranded silver-plated copper |
| Dielectric  |             | High-temperature fluoropolymer       |
| Shield 1  |             | Aluminum tape                        |
| Shield 2  |             | Silver-plated copper braid           |
| Outer Jacket  |             | White high-temperature fluoropolymer |
| Skydrol is a protected trademark of the Eastman Chemical Company. |             |                                      |



Learn More: Amphenol-CIT.com

+1 (800) 458-9960