


Semi-Rigid Coaxial Cables

P/N UT-056 | 50 Ω Copper Outer Conductor

INTRODUCTION



All of our 50 Ω copper semi-rigid cables feature low attenuation and VSWR covering the entire microwave spectrum. With numerous connector options available off-the-shelf, this family of cables is one of the most versatile available today. They meet the demands of package density and provide total shielding for elimination of signal loss and noise.

DIMENSIONS

Outer Conductor Diameter	in	0.056 ± 0.002
	mm	1.422 ± 0.051
Center Conductor Diameter	in	0.0113
	mm	0.2870
Length (Maximum)	Feet	20
	Meter	6.10

MATERIALS

Outer Conductor	Copper
Outer Conductor Plating	None
Dielectric	PTFE
Center Conductor	SPCW
RoHS Compliant	✓

MECHANICAL CHARACTERISTICS*

Outer Conductor Integrity Temp.	°C	200
Operating Temperature (Max)	°C	175
Inside Bend Radius (Minimum)	in	0.125
	mm	3.175
Weight	lbs / 100ft	0.70
	kg / 100m	1.05

* Applicable at room temperature. Contact factory for performance over temperature range.

ELECTRICAL CHARACTERISTICS*

Characteristic Impedance	ohm	50
Capacitance	pF / ft	29.0
	pF / m	95.2
Corona Extinction Voltage	VRMS @ 60 Hz	1500
Voltage Withstanding	VRMS @ 60 Hz	3000
Higher Order Mode Frequency	GHz	109.0
Attenuation (Db / 100 Ft Typical)	@ 0.5 GHz	24
	@ 1.0 GHz	34.2
	@ 5.0 GHz	78.8
	@ 10.0 GHz	113.8
	@ 18.0 GHz	156.5
	@ 26.5 GHz	193.8
	@ 40.0 GHz	244.2
	@ 50.0 GHz	277.5
	@ 65.0 GHz	323
Power (Watts Cw @ 20 °C, Maximum)	@ 0.5 GHz	110.4
	@ 1.0 GHz	77.6
	@ 5.0 GHz	34
	@ 10.0 GHz	23.6
	@ 18.0 GHz	17.3
	@ 26.5 GHz	14
	@ 40.0 GHz	11.2
	@ 50.0 GHz	9.9
	@ 65.0 GHz	8.5
@ 90.0 GHz	7.1	