## **ECS Avionics RF Cable**

## P/N 361201 | 50 Ω Coaxial



## INTRODUCTION

Our ECS Brand Avionics RF cables are optimized specifically for avionics systems that require a low-loss, lightweight, halogen-free cable with frequencies between 0 - 12 GHz. Sold in bulk, as finished assemblies, or within an application-specific kit, these cables have short lead times and are often in stock with same-day shipping available.

## **ENVIRONMENTAL DETAILS**

- » Designed to meet or exceed burn requirements as set forth in Federal Aviation Regulations 14 CFR Part 25.869(a)(4) Amdt 25-113, Appendix F Part I(a)(3).
- » Manufactured with materials which, when subjected to flames or high temperatures, will not outgas deadly hydrogen chloride produced by conventional PVC cables.

CONNECTOR TYPE	P/N	
ARINC 404 Size 1	LMT101 Adapter	
ARINC 600 Size 1	N-A	
ARINC 600 Size 1 Modified	N-A	
ARINC 600 Size 5	N-A	
ARINC 600 Size 8	N-A	
BNC 90°	N-A	
BNC 90° Extended	N-A	
BNC 90° Long	N-A	
BNC Bulkhead	N-A	
BNC Straight	CBS6222	
C 90°	CCR6222	
C Straight	N-A	
HN 90°	N-A	
N 90°	N-A	
N Bulkhead	N-A	
N Straight	N-A	
SMA 90°	N-A	
SMA Straight	N-A	
TNC 90°	N-A	
TNC 90° Self-Locking	CLTR6222	
TNC 90° Extended	N-A	
TNC 90° Long	N-A	
TNC Bulkhead	N-A	
TNC Panel Mount	N-A	
TNC Straight	N-A	
TNC Straight Self-Locking CLTS6222		

PHYSICA	AL CHARACT	TERISTICS (NOMINAL)
Outer Diameter		0.325"
Minimum Bend Radius		1.7"
Weight		8.8 lb/100 ft
Temperature Range		-55 to 150 °C
Skydrol™ Resistant		Yes
ELECTR	CAL CHARA	CTERISTICS (NOMINAL)
Impedance		50 Ω
Capacitance		25.0 pF/ft
DC Resistance		1.26 Ω/1,000 ft
Time Delay		1.27 ns/ft
Velocity of Propagation		80%
Shield Effect	iveness	> 90 dB
Attenuation	@ 156 MHz	1.8 dB/100 ft
	@ 1,090MHz	5.0 dB/100 ft
	@ 1,660 MHz	6.0 dB/100 ft
	@ 2,400 MHz	7.2 dB/100 ft
	@ 5,091 MHz	10.3 dB/100 ft
CONSTR	RUCTION DE	TAILS
Conductor		12 AWG solid silver-plated copper
Dielectric		Low-density, high-temperature fluoropolymer
Shield 1		Silver-plated copper braid
Shield 2		Aluminum/polyester foil
Shield 3		Silver-plated copper wire braid
Outer Jacket		White high-temperature fluoropolymer (laser markable)





Learn More: Amphenol-CIT.com

+1 (800) 458-9960